

# BARRIER FLUID TOTE



## KEY FEATURES

- Capable of adding new barrier fluid into a pressurized system or unpressurized system.
- Ease of use - rugged, easy-to-maneuver cart with heavy duty casters.

## PERFORMANCE

- 30-gallon stainless steel reservoir with hand pump mounted, with heavy duty casters for easy handling.
- Pre-Assembled Unit.
- Quick disconnects to reduce leaks.
- Hose reel for easy use.
- Discharge supply filters micron size to be determined per application.
- Clean out covers for easy maintenance.
- Trap

## OPERATING SPECIFICATIONS

- Maximum operating pressure: 750 psig
- High Flow: 20 gallons/100 strokes
- High Pressure: 1.84 inS/stroke

## COMPONENTS

• Reservoir	• Gauges	• Hose Reel	• Breather
• Valves	• Quick Disconnects	• Filter	
• Pumps	• Sight Glass	• System Relief	



24/7/365 Live-Support, Day or Night.



**CONTACT US**  
800-722-2630



*Powering American Industry*

*CFI 21-025 Design*



## CFI CORPORATE

WORLDWIDE SERVICE: TEXAS & BEYOND



7725 South Major Drive  
Beaumont, TX 77705



800-722-2630



isales@confluids.com

### LOUISIANA

Serving Louisiana & Mississippi

**337-205-0900**

204 Jared Drive  
Broussard, LA 70518

### OKLAHOMA

Serving Oklahoma, Arkansas  
& Kansas

**918-251-7065**

2009 North Willow Avenue,  
Broken Arrow, OK 74012

### ROCKY MOUNTAINS

Serving Wyoming, Colorado,  
& New Mexico

**918-251-7065**

2009 North Willow Avenue,  
Broken Arrow, OK 74012



[www.confluids.com](http://www.confluids.com)

Rev. July 2024